

Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010

Jara Bato 00/2010

Board Rev. 1 Page

Document n° 134/09

Revision date 14.02.2022

Rev. N°

Edited by RLAB

Approved by DG

Filed by RLAB

1 di 14

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: Product name UFI: F_136

ALCOOL Etilico 90° Profumato AMACASA

7PC0-S0A7-U00T-M5QN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses cleaner for hard surfaces

Industrial

Professional

Consumer

Uses Advised Against

Do not use for uses other than those indicated

1.3. Details of the supplier of the safety data sheet

Name Full address District and Country NEW FADOR S.r.l. via Mario Calderara, 31 25018 Montichiari (BS) Italia

Tel. +39 030961 243

www.newfador.it

e-mail address of the competent person

responsible for the Safety Data Sheet

info@newfador.it

1.4. Emergency telephone number

For urgent inquiries refer to

NEW FADOR S.r.I.

+39 030961 243

(08.30 - 17.30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2
Eye irritation, category 2

H225 H319 Highly flammable liquid and vapour. Causes serious eye irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words:

Danger

Hazard statements:

H225 Highly flammable liquid and vapour.H319 Causes serious eye irritation.

Precautionary statements:



Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2

Board Date 05/2010

Board Rev. 1

Document n° Revision date Rev. N° Edited by Approved by Filed by Page 134/09 14.02.2022 10 RLAB DG RLAB 2 di 14

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P370+P378 In case of fire: use anhydride carbon (CO2) to extinguish.

P501 Dispose of contents/container in accordance to current regulation.

Ingredients according to Regulation (EC) No. 648/2004

perfumes, Alpha-Isomethyl Ionone, Citronellol, Coumarin, Hexyl Cinnamal, Linalool

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

ETHANOL

CAS 64-17-5 82 ≤ x < 86 Flam. Liq. 2 H225,

Eye Irrit. 2 H319

EC 200-578-6 INDEX 603-002-00-5

REACH Reg. 01-2119457610-43

METHYL ETHYL KETONE

CAS 78-93-3 $0.9 \le x < 1$ Flam. Liq. 2 H225,

Eye Irrit. 2 H319, STOT SE 3 H336,

EUH066

EC 201-159-0 INDEX 606-002-00-3

REACH Reg. 01-2119457290-43

TOLUENE

CAS 108-88-3 $0 \le x < 0.05$ Flam. Liq. 2 H225,

Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336

EC 203-625-9 INDEX 601-021-00-3

REACH Reg. 01-2119471310-51-

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

No episodes of harm to the staff authorised to use the product have been reported. The following general measures should be adopted as necessary:

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Do not give anything by mouth to an unconscious



Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010

Board Rev. 1

Document n° 134/09

Revision date 14.02.2022

RLAB

Approved by DG

Filed by RLAB

Page 3 di 14

person.

EYES and SKIN: Wash with plenty of water. In the event of persistent irritation, get medical advice/attention.

Rev. N°

10

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage



Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010

Board Rev. 1

Document n°Revision dateRev. N°Edited byApproved byFiled byPage134/0914.02.202210RLABDGRLAB4 di 14

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well-ventilated place, away from direct sunlight. Store in a cool and well-ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή
		μεταλλαξιγόνους παράγοντες κατά την εργασία`»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők
11011	Magyarorozag	hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmienama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu.
	valena	graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste
		lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes
		químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à
		exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie
		w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w
		środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea
		și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády
		Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s
		expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list
		RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive
		2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

ETHANOL Threshold Limit Value							
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		



Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1

134/09

Revision date 14.02.2022

Rev. N° Edited by RLAB

Approved by DG

Filed by RLAB

Page 5 di 14

TLV	BGR	1000						
TLV	CZE	1000		3000				
AGW	DEU	960	500	1920	1000			
MAK	DEU	960	500	1920	1000			
TLV	DNK	1900	1000					
VLA	ESP			1910	1000			
VLEP	FRA	1900	1000	9500	5000			
TLV	GRC	1900	1000					
AK	HUN	1900		7600				
GVI/KGVI	HRV	1900	1000					
TGG	NLD	260		1900		SKIN		
NDS/NDSCh	POL	1900						
NPEL	SVK	960	500	1920				
WEL	GBR	1920	1000					
TLV-ACGIH				1884	1000			
Predicted no-effect concer	ntration - PNEC							
Normal value in fresh water	er			0,96	mç	g/l		
Normal value in marine wa	ater			0,79	mç	g/l		
Normal value for fresh wat	er sediment			3,6	mg	g/kg		
Normal value for marine w	ater sediment			2,9	mç	g/kg		
Normal value for water, int	ermittent release			2,75	mg	g/l		
Normal value of STP micro	oorganisms			580	mç	g/l		
Normal value for the food	chain (secondary poiso	oning)		0,38	mg	g/kg		
Normal value for the terres	strial compartment			0,63	mg	g/kg		
Health - Derived no-en	ffect level - DNEL / Effects on consumers	DMEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				87 mg/kg bw/d				
Inhalation				114 mg/m3				950 mg/m3
Skin				206 mg/kg bw/d				343 mg/kg bw/d

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	590		885		
TLV	CZE	600		900		
AGW	DEU	600	200	600	200	SKIN
MAK	DEU	600	200	600	200	SKIN
TLV	DNK	145	50			SKIN
VLA	ESP	600	200	900	300	
VLEP	FRA	600	200	900	300	SKIN
TLV	GRC	600	200	900	300	
AK	HUN	600		900		
GVI/KGVI	HRV	600	200	900	300	SKIN
VLEP	ITA	600	200	900	300	
VLE	PRT	600	200	900	300	
NDS/NDSCh	POL	450		900		
NPEL	SVK	600	200	900		
WEL	GBR	600	200	899	300	SKIN
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	
Predicted no-effect conc	entration - PNEC					
Normal value in fresh wa	iter			55,8	m	g/l



Conforms to Reg. (EU) 878/2020

RLAB

Board Code S-P4/2-2
Board Date 05/2010
Board Rev. 1

134/09

Oral

Revision date Rev. N° Edited by Approved by

10

14.02.2022

proved by Filed by RLAB

Page 6 di 14

Normal value in marine water					mg	g/l		
Normal value for fresh water sediment					mç	g/kg		
Normal value for marine water sediment				284,7	mg	g/kg		
Normal value for water, inte	ermittent release			55,8	mg/l			
Normal value of STP microorganisms				709	mg/l			
Normal value for the food c	hain (secondary poisoni	ng)		1000	mg/kg			
Normal value for the terrest	rial compartment			22,5	mç	g/kg		
Health - Derived no-eff	ect level - DNEL / D	MEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic

 bw/d

 Inhalation
 106 mg/m3
 600 mg/m3

 Skin
 412 mg/kg bw/d
 1161 mg/kg bw/d

31 mg/kg

Туре	Country	TWA/8h		STEL/15min		Remarks /	
		mg/m3	ppm	mg/m3	ppm	Observations	
TLV	BGR	150		300			
TLV	CZE	200		500		SKIN	
AGW	DEU	190	50	760	200	SKIN	
MAK	DEU	190	50	760	200		
TLV	DNK	94	25			SKIN	
VLA	ESP	192	50	384	100	SKIN	
VLEP	FRA	76,8	20	384	100	SKIN	
TLV	GRC	192	50	384	100		
AK	HUN	190		760			
GVI/KGVI	HRV	192	50	384	100	SKIN	
VLEP	ITA	192	50			SKIN	
TGG	NLD	150		384			
VLE	PRT	192	50	384	100	SKIN	
NDS/NDSCh	POL	100		200			
TLV	ROU	192	50	384	100	SKIN	
NPEL	SVK	192	50	384		SKIN	
MV	SVN	192	50	384	100	SKIN	
WEL	GBR	191	50	384	100	SKIN	
OEL	EU	192	50	384	100	SKIN	
TLV-ACGIH		75,4	20				
Predicted no-effect conc	entration - PNEC						
Normal value in fresh wa	ter			0,68	m	g/l	
Normal value in marine water			0,68	m	g/l		
Normal value for fresh water sediment			16,39	m	g/kg/d		
Normal value for marine water sediment			16,39	m	g/kg/d		
Normal value for water, intermittent release			0,68	m	ŋ/l		
Normal value of STP microorganisms			13,61	m	ŋ/l		
Normal value for the food	d chain (secondary poiso	oning)		2,89	m	g/kg soil dw	

Normal value for the food chain (secondary poisoning)				2,89	mg	ı/kg soil dw		
Health - Derived no-effe	ect level - DNEL / D	MEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				8,13 mg/kg bw/d				
Inhalation	226 mg/m3	226 mg/m3	56,5 mg/m3	56,5 mg/m3	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3
Skin				226 mg/kg bw/d				384 mg/kg bw/d



Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010

Board Rev. 1

Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page
134/09	14.02.2022	10	RLAB	DG	RLAB	7 di 14

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Information

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value
Appearance	liquid
Colour	red
Odour	characteristic
Melting point / freezing point	Not available
Initial boiling point	< 80 °C
Flammability	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Flash point	< 15 °C
Auto-ignition temperature	Not available
pH	Not available
Kinematic viscosity	Not available
Dynamic viscosity	1.2 mPa*s (riferito all'etanolo)
Solubility	soluble in water

Partition coefficient: n-octanol/water Not available Vapour pressure Not available Density and/or relative density 0,826 g/ml Relative vapour density Not available Particle characteristics Not applicable

9.2. Other information



Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2

Board Date 05/2010

Board Rev. 1

Document n° Revision date Rev. N° Edited by Approved by Filed by Page 134/09 14.02.2022 10 RLAB DG RLAB 8 di 14

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Explosive properties readily combustible and misuse may result in burns or

uncontrolled fires

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

METHYL ETHYL KETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

TOLUENE

Avoid exposure to: light.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHANOL

Risk of explosion on contact with: alkaline metals, alkaline oxides, calcium hypochlorite, sulphur monofluoride, acetic anhydride, acids, concentrated hydrogen peroxide, perchlorates, perchloric acid, perchloronitrile, mercury nitrate, nitric acid, silver, silver nitrate, ammonia, silver oxide, ammonia, strong oxidising agents, nitrogen dioxide. May react dangerously with: bromoacetylene, chlorine acetylene, bromine trifluoride, chromium trioxide, chromyl chloride, fluorine, potassium tert-butoxide, lithium hydride, phosphorus trioxide, black platinum, zirconium (IV) chloride, zirconium (IV) iodide. Forms explosive mixtures with: air.

METHYL ETHYL KETONE

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHANOL

Avoid exposure to: sources of heat, naked flames.

METHYL ETHYL KETONE

Avoid exposure to: sources of heat.

10.5. Incompatible materials

METHYL ETHYL KETONE

Incompatible with: strong oxidants, inorganic acids, ammonia, copper, chloroform.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.



Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010

and David

Board Rev. 1

Document n° 134/09

Revision date 14.02.2022

Rev. N° Edited by RLAB

Approved by DG

Filed by RLAB

Page 9 di 14

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

ATE (Dermal) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

Not classified (no significant component)

ETHANOL

LD50 (Oral): > 5000 mg/kg Rat

LC50 (Inhalation vapours): 120 mg/l/4h Pimephales promelas

METHYL ETHYL KETONE

 LD50 (Dermal):
 6480 mg/kg Rabbit

 LD50 (Oral):
 2737 mg/kg Rat

 LC50 (Inhalation vapours):
 23,5 mg/l/8h Rat

TOLUENE

LD50 (Dermal): > 5000 mg/kg bw Rabbit
LD50 (Oral): > 5000 mg/kg bw Rat
LC50 (Inhalation vapours): 100 ppm human

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999). The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available



Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010

Board Rev. 1

Document n° Revision date Rev. N° Edited by Approved by Filed by Page 134/09 14.02.2022 10 RLAB DG RLAB 10 di 14

Route of exposure Information not available ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

TOLUENE

LC50 - for Fish 5,5 mg/l/96h Oncorhynchus kisutch

EC50 - for Crustacea 3,78 mg/l

EC50 - for Algae / Aquatic Plants 134 mg/l/3 h Chlorella vulgaris and Chlamydomonas angulosa

Chronic NOEC for Algae / Aquatic Plants 10 mg/l/72 h Skeletonema costatum

ETHANOL

LC50 - for Fish 14200 mg/l/96h
EC50 - for Crustacea 454 mg/l/48h
EC50 - for Algae / Aquatic Plants 275 mg/l/72h
Chronic NOEC for Fish 250 mg/l
Chronic NOEC for Crustacea 96 mg/l
Chronic NOEC for Algae / Aquatic Plants 11,5 mg/l

METHYL ETHYL KETONE

LC50 - for Fish 1656 mg/l/72h EC50 - for Algae / Aquatic Plants 1972 mg/l/72h

12.2. Persistence and degradability

TOLUENE

Solubility in water 100 - 1000 mg/l

Rapidly degradable

ETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

METHYL ETHYL KETONE

Solubility in water > 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

TOLUENE

Partition coefficient: n-octanol/water 2,73 BCF 90

ETHANOL

Partition coefficient: n-octanol/water -0,35

METHYL ETHYL KETONE

Partition coefficient: n-octanol/water 0,3

12.4. Mobility in soil



Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010

Board Rev. 1

Filed by Page **RLAB**

Document n°	Revision date
134/09	14.02.2022

Rev. N° 10

Edited by **RLAB**

Approved by DG

11 di 14

TOLUENE

2,31 Partition coefficient: soil/water

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG,

1987

14.2. UN proper shipping name

ADR / RID: ALCOHOLS, N.O.S. IMDG: ALCOHOLS, N.O.S. IATA: ALCOHOLS, N.O.S.

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

14.4. Packing group

ADR / RID, IMDG,

IATA:

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO



134/09

MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010

Board Rev. 1

Revision date Rev. N° Edited by Approved by Filed by Page
14.02.2022 10 RLAB DG RLAB 12 di 14

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 33

Limited Tunnel Quantities: 1 restriction

code: (D/E)

Special provision: 640D

EMS: F-E, S-D Limited
Quantities: 1

L

IATA: Cargo: Maximum Packaging

quantity: 60 L instructions:

364

Pass.: Maximum Packaging quantity: 5 L instructions:

353

A3, A180

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

IMDG:

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provision:

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment



134/09

MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

RLAB

DG

Board Code S-P4/2-2 Board Date 05/2010

Board Rev. 1

Filed by	Page
RLAB	13 di 14

Revision date Rev. N° Edited by Approved by Document nº Filed by

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

10

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

14.02.2022

Flam. Liq. 2 Flammable liquid, category 2 Repr. 2 Reproductive toxicity, category 2 Asp. Tox. 1 Aspiration hazard, category 1

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H225 Highly flammable liquid and vapour. H361d Suspected of damaging the unborn child. H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)

Documen³

MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Board Code S-P4/2-2 Board Date 05/2010

Board Rev. 1

Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page
134/09	14.02.2022	10	RLAB	DG	RLAB	14 di 14

- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP) 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11. Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified:

01/02/03/08/09/10/11/12/14/15/16.