



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

1 of 15

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Code: 21010000079  
Product name: DENTAURATED ETHYL ALCOHOL 90°  
UFI: 6VV1-XGX9-CHMK-WXRP

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
hard surface cleaner	-	✓	✓
Uses Advised Against			

Do not use for uses other than those indicated

### 1.3. Details of the supplier of the safety data sheet

Name: NEW FADOR S.r.l.  
Full address: via Mario Calderara, 31  
District and Country: 25018 Montichiari (BS)  
Italia  
Tel. +39 030961 243  
[www.newfador.it](http://www.newfador.it)

e-mail address of the competent person responsible for the Safety Data Sheet: [info@newfador.it](mailto:info@newfador.it)

### 1.4. Emergency telephone number

For urgent inquiries refer to: NEW FADOR S.r.l.  
+39 030961 243  
(08.30 - 17.30)

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

2 of 15



Signal words:

Danger

Hazard statements:

**H225** Highly flammable liquid and vapour.  
**H319** Causes serious eye irritation.

Precautionary statements:

**P101** If medical advice is needed, have product container or label at hand.  
**P102** Keep out of reach of children.  
**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P370+P378** In case of fire: use anhydride carbon (CO<sub>2</sub>) to extinguish.  
**P403+P235** Store in a well-ventilated place. Keep cool.  
**P501** Dispose of contents/container in accordance to current regulation.

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.1. Substances

Information not relevant

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>ETHANOL</b>		
CAS 64-17-5	$82 \leq x < 86$	Flam. Liq. 2 H225, Eye Irrit. 2 H319
EC 200-578-6		Eye Irrit. 2 H319: $\geq 50\%$
INDEX 603-002-00-5		
REACH Reg. 01-2119457610-43		
<b>METHYL ETHYL KETONE</b>		
CAS 78-93-3	$0,9 \leq x < 1$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 201-159-0		
INDEX 606-002-00-3		
REACH Reg. 01-2119457290-43		



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

3 of 15

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

No episodes of harm to the staff authorised to use the product have been reported. The following general measures should be adopted as necessary:  
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.  
INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Do not give anything by mouth to an unconscious person.  
EYES and SKIN: Wash with plenty of water. In the event of persistent irritation, get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

4 of 15

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

## 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

## 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well-ventilated place, away from direct sunlight. Store in a cool and well-ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

3

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte.



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

5 of 15

DNK	Danmark	MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
FRA	France	Límites de exposición profesional para agentes químicos en España 2021
GRC	Ελλάδα	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
		Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ `σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία`»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

## ETHANOL Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	BGR	1000				
TLV	CZE	1000		3000		
AGW	DEU	960	500	1920	1000	
MAK	DEU	960	500	1920	1000	
TLV	DNK	1900	1000			
VLA	ESP			1910	1000	
VLEP	FRA	1900	1000	9500	5000	
TLV	GRC	1900	1000			
AK	HUN	1900		7600		
GVI/KGVI	HRV	1900	1000			
TGG	NLD	260		1900	SKIN	
NDS/NDSch	POL	1900				
NPEL	SVK	960	500	1920		
WEL	GBR	1920	1000			
TLV-ACGIH				1884	1000	
Predicted no-effect concentration - PNEC						
Normal value in fresh water				0,96	mg/l	
Normal value in marine water				0,79	mg/l	
Normal value for fresh water sediment				3,6	mg/kg	
Normal value for marine water sediment				2,9	mg/kg	



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

6 of 15

Normal value for water, intermittent release	2,75	mg/l
Normal value of STP microorganisms	580	mg/l
Normal value for the food chain (secondary poisoning)	0,38	mg/kg
Normal value for the terrestrial compartment	0,63	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				87 mg/kg bw/d				
Inhalation				114 mg/m3				950 mg/m3
Skin				206 mg/kg bw/d				343 mg/kg bw/d

## METHYL ETHYL KETONE

### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	590		885		
TLV	CZE	600		900		
AGW	DEU	600	200	600	200	SKIN
MAK	DEU	600	200	600	200	SKIN
TLV	DNK	145	50			SKIN
VLA	ESP	600	200	900	300	
VLEP	FRA	600	200	900	300	SKIN
TLV	GRC	600	200	900	300	
AK	HUN	600		900		
GVI/KGVI	HRV	600	200	900	300	SKIN
VLEP	ITA	600	200	900	300	
VLE	PRT	600	200	900	300	
NDS/NDSCh	POL	450		900		
NPEL	SVK	600	200	900		
WEL	GBR	600	200	899	300	SKIN
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	

## Predicted no-effect concentration - PNEC

Normal value in fresh water	55,8	mg/l
Normal value in marine water	55,8	mg/l
Normal value for fresh water sediment	284,74	mg/kg
Normal value for marine water sediment	284,7	mg/kg
Normal value for water, intermittent release	55,8	mg/l
Normal value of STP microorganisms	709	mg/l
Normal value for the food chain (secondary poisoning)	1000	mg/kg
Normal value for the terrestrial compartment	22,5	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

7 of 15

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				31 mg/kg bw/d				
Inhalation				106 mg/m3				600 mg/m3
Skin				412 mg/kg bw/d				1161 mg/kg bw/d

## Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

## HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

## SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

## EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

## RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

## ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	red	



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

8 of 15

Odour	characteristic	
Odour threshold	18,8 mg/m <sup>3</sup>	
Melting point / freezing point	-114 °C	
Initial boiling point	78 °C	
Flammability (solid, gas)	not applicable	
Lower explosive limit	2,5 % (v/v)	
Upper explosive limit	13,5 % (v/v)	
Flash point	13 °C	
Auto-ignition temperature	363 °C	
Decomposition temperature	not available	
pH	7	
Kinematic viscosity	not available	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	-0,35	Temperature: 20 °C
Vapour pressure	5726 Pa (20°C)	
Density and/or relative density	0,7844	
Relative vapour density	not available	
Particle characteristics	not applicable	

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

Information not available

### 9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	86,96 % - 682,11 g/litre
VOC (volatile carbon)	45,52 % - 357,06 g/litre
Explosive properties	not classified as explosive, contains no explosive substances according to CLP Art. (14 (2))
Oxidising properties	the product is not an oxidizing substance

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### METHYL ETHYL KETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.





# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

9 of 15

## 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

### ETHANOL

Risk of explosion on contact with: alkaline metals, alkaline oxides, calcium hypochlorite, sulphur monofluoride, acetic anhydride, acids, concentrated hydrogen peroxide, perchlorates, perchloric acid, perchloronitrile, mercury nitrate, nitric acid, silver, silver nitrate, ammonia, silver oxide, ammonia, strong oxidising agents, nitrogen dioxide. May react dangerously with: bromoacetylene, chlorine acetylene, bromine trifluoride, chromium trioxide, chromyl chloride, fluorine, potassium tert-butoxide, lithium hydride, phosphorus trioxide, black platinum, zirconium (IV) chloride, zirconium (IV) iodide. Forms explosive mixtures with: air.

### METHYL ETHYL KETONE

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

## 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

### ETHANOL

Avoid exposure to: sources of heat, naked flames.

### METHYL ETHYL KETONE

Avoid exposure to: sources of heat.

## 10.5. Incompatible materials

### METHYL ETHYL KETONE

Incompatible with: strong oxidants, inorganic acids, ammonia, copper, chloroform.

## 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

#### Information on likely routes of exposure

Information not available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

#### Interactive effects

Information not available

#### ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

10 of 15

## ETHANOL

LD50 (Oral):

> 5000 mg/kg Rat

LC50 (Inhalation vapours):

120 mg/l/4h Pimephales promelas

## METHYL ETHYL KETONE

LD50 (Dermal):

6480 mg/kg Rabbit

LD50 (Oral):

2737 mg/kg Rat

LC50 (Inhalation vapours):

23,5 mg/l/8h Rat

### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

#### Respiratory sensitization

Information not available

#### Skin sensitization

Information not available

### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### Adverse effects on sexual function and fertility

Information not available

#### Adverse effects on development of the offspring

Information not available

#### Effects on or via lactation

Information not available

### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

#### Target organs

Information not available

#### Route of exposure

Information not available

### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### Target organs

Information not available

#### Route of exposure

Information not available

### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity

ETHANOL



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

11 of 15

LC50 - for Fish	14200 mg/l/96h
EC50 - for Crustacea	454 mg/l/48h
EC50 - for Algae / Aquatic Plants	275 mg/l/72h
Chronic NOEC for Fish	250 mg/l
Chronic NOEC for Crustacea	96 mg/l
Chronic NOEC for Algae / Aquatic Plants	11,5 mg/l

## METHYL ETHYL KETONE

LC50 - for Fish	1656 mg/l/72h
EC50 - for Algae / Aquatic Plants	1972 mg/l/72h

### 12.2. Persistence and degradability

#### ETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

#### METHYL ETHYL KETONE

Solubility in water > 10000 mg/l

Rapidly degradable

### 12.3. Bioaccumulative potential

#### ETHANOL

Partition coefficient: n-octanol/water -0,35

#### METHYL ETHYL KETONE

Partition coefficient: n-octanol/water 0,3

### 12.4. Mobility in soil

Information not available

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

### 12.7. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

12 of 15

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1170

### 14.2. UN proper shipping name

ADR / RID: ETHANOL

IMDG: ETHANOL

IATA: ETHANOL

### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



### 14.4. Packing group

ADR / RID, IMDG, IATA: II

### 14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

### 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 33

Special provision: -

IMDG: EMS: F-E, S-D

IATA: Cargo:

Limited  
Quantities: 1  
L

Limited  
Quantities: 1  
L

Maximum  
quantity: 60 L

Tunnel  
restriction  
code: (D/E)

Packaging  
instructions:



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

13 of 15

Pass.:

Maximum  
quantity: 5 L

364  
Packaging  
instructions:  
353

Special provision:

A3, A58,  
A180

## 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product  
Point 3 - 40

Contained substance  
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

Substances in Candidate List (Art. 59 REACH)  
On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)  
None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:  
None

Substances subject to the Rotterdam Convention:  
None

Substances subject to the Stockholm Convention:  
None

Healthcare controls  
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)  
WGK 1: Low hazard to waters

### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

14 of 15

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H319</b>	Causes serious eye irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)



# MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

Issued on 25/01/2018

Revision n° 5

Rev. Date 22/08/2022

Page

15 of 15

- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

#### Changes to previous review:

The following sections were modified:

02 / 03 / 09 / 11 / 12 / 15 / 16.