

	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	1 di 13

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: TERZI35
 Product name: CRISTAL PER VETRI E CRISTALLI AMACASA
 UFI: VK34-HPK2-9A2J-3TAU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
glass cleaner	-	✓	✓

Uses Advised Against

Do not use for uses other than those indicated

1.3. Details of the supplier of the safety data sheet

Name: NEW FADOR S.r.l.
 Full address: via Mario Calderara, 31
 District and Country: 25018 Montichiari (BS)
 Italia
 Tel. +39 030961 243
 www.newfador.it

e-mail address of the competent person responsible for the Safety Data Sheet: info@newfador.it

1.4. Emergency telephone number

For urgent inquiries refer to: NEW FADOR S.r.l.
 +39 030961 243
 (08.30 - 17.30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 3 H229 Pressurised container: may burst if heated.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: Warning

Hazard statements:

H229 Pressurised container: may burst if heated.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	2 di 13

Ingredients according to Regulation (EC) No. 648/2004

5% or over but less than aliphatic hydrocarbons
15%

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
Hydrocarbons, C3-4 CAS 68476-40-4 EC 270-681-9 INDEX 649-199-00-1 REACH Reg. 01-2119486557-22	$9 \leq x < 10,5$	Flam. Gas 1A H220, Press. Gas H280
1-methoxypropan-2-ol CAS 107-98-2 EC 203-539-1 INDEX - REACH Reg. 01-2119457435-35	$4,5 \leq x < 5$	Flam. Liq. 3 H226, STOT SE 3 H336
3-BUTOXY-2-PROPANOL CAS 5131-66-8 EC 225-878-4 INDEX 603-052-00-8 REACH Reg. 01-2119475527-28	$4,5 \leq x < 5$	Eye Irrit. 2 H319, Skin Irrit. 2 H315
ETHANOLAMINE CAS 141-43-5 EC 205-483-3 INDEX 603-030-00-8 REACH Reg. 01-2119486455-28	$0,809 \leq x < 0,909$	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335 STOT SE 3 H335: $\geq 5\%$ LD50 Oral: >500 bw, STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures


4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person,

	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	3 di 13

unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing

	<h1 style="text-align: center;">MATERIAL SAFETY DATA SHEET</h1> <p style="text-align: center;">Conforming to Reg. (EU) 878/2020</p>					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	4 di 13

transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well-ventilated place, away from direct sunlight. Store in a cool and well-ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):
2B

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία``»
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2017/164; Directive 2000/39/EC; Directive 98/24/EC; ACGIH 2020
	TLV-ACGIH	

Hydrocarbons, C3-4

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic systemic	Effects on workers			Chronic systemic
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local	
Inhalation				0.066 mg/m3				2.21 mg/m3
Skin								23.4 mg/kg bw/d

3-BUTOXY-2-PROPANOL

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,525	mg/l
Normal value in marine water	0,052	mg/l



MATERIAL SAFETY DATA SHEET

Conforming to Reg. (EU) 878/2020

Sheet Code S-P4/2-2

Sch. Date 05/2010

Sheet Rev.1

Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	5 di 13

Normal value for fresh water sediment	2,36	mg/kg
Normal value for marine water sediment	0,236	mg/kg
Normal value for water, intermittent release	5,25	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,16	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				12,5 mg/kg bw/d				
Inhalation				43 mg/m3				147 mg/m3
Skin				22 mg/kg bw/d				52 mg/kg bw/d

1-methoxypropan-2-ol

Predicted no-effect concentration - PNEC

Normal value in fresh water	10	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	52,3	mg/kg/d
Normal value for marine water sediment	5,2	mg/kg/d
Normal value for water, intermittent release	100	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	4,59	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				33 mg/kg bw/d				33
Inhalation				43,9 mg/m3	553,5 mg/m3	553,5 mg/m3		369 mg/m3
Skin				78 mg/kg bw/d				183 mg/kg bw/d

ETHANOLAMINE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	8		15		
TLV	CZE	2,5		7,5		SKIN
AGW	DEU	5,1	2	10,2	4	SKIN
MAK	DEU	5,1	2	10,2	4	
TLV	DNK	2,5	1			SKIN
VLA	ESP	2,5	1	7,5	3	SKIN
VLEP	FRA	2,5	1	7,6	3	SKIN
TLV	GRC	2,5	1	7,6	3	
GVI/KGVI	HRV	2,5	1	7,6	3	SKIN
VLEP	ITA	2,5	1	7,6	3	SKIN
TGG	NLD	2,5		7,6		SKIN
VLE	PRT	2,5	1	7,6	3	SKIN
NDS/NDSch	POL	2,5		7,5		
MV	SVN	2,5	1			SKIN
WEL	GBR	2,5	1	7,6	3	SKIN
OEL	EU	2,5	1	7,6	3	SKIN
TLV-ACGIH		7,5	3	15	6	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,085	mg/l
Normal value in marine water	0,009	mg/l
Normal value for fresh water sediment	0,434	mg/kg/d



MATERIAL SAFETY DATA SHEET

Conforming to Reg. (EU) 878/2020

Sheet Code S-P4/2-2

Sch. Date 05/2010

Sheet Rev.1

Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	6 di 13

Normal value for marine water sediment	0,043	mg/kg/d
Normal value for water, intermittent release	0,028	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,037	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				3,75 mg/kg bw/d				
Inhalation			2 mg/m3				3,3 mg/m3	
Skin				0,24 mg/kg bw/d				1 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.


ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	white	
Odour	characteristic	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Flammability	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	Not available	
Auto-ignition temperature	Not available	

	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	7 di 13

Decomposition temperature	Not available
pH	10
Kinematic viscosity	Not available
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Vapour pressure	3,2 Bar
Density and/or relative density	1 g/cm ³
Relative vapour density	>2
Particle characteristics	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes
Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EC)	5,80 % - 58,00 g/litre
VOC (volatile carbon)	3,44 % - 34,40 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHANOLAMINE

May react dangerously with: acrylonitrile, chloroepoxypropane, chlorosulphuric acid, hydrogen chloride, iron-sulphur compounds, acetic acid, acetic anhydride, mesityl oxide, nitric acid, sulphuric acid, strong acids, vinyl acetate, cellulose nitrate.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHANOLAMINE

Avoid exposure to: air, sources of heat.

10.5. Incompatible materials

ETHANOLAMINE

Incompatible with: iron, strong acids, strong oxidants.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.


ETHANOLAMINE

May develop: nitric oxide, carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the

	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	8 di 13

toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)
 ATE (Oral) of the mixture: Not classified (no significant component)
 ATE (Dermal) of the mixture: Not classified (no significant component)

Hydrocarbons, C3-4

LC50 (Inhalation mists/powders): 505 mg/l/10 rat (10 min)

3-BUTOXY-2-PROPANOL

LD50 (Oral): > 2000 mg/kg bw Female Rat
 LD50 (Dermal): > 2000 mg/kg Rat

1-methoxypropan-2-ol

LD50 (Oral): 3739 mg/kg bw Male Rat
 LD50 (Dermal): > 2000 mg/kg bw Rat
 LC50 (Inhalation vapours): < 6000 ppm/6h Female Mouse

ETHANOLAMINE

LD50 (Oral): > 500 bw Female Mouse
 LD50 (Dermal): 2504 mg/kg bw Male Rabbit
 STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
 (figure used for calculation of the acute toxicity estimate of the mixture)
 LC50 (Inhalation vapours): > 1,3 mg/l air/6 h Rat
 STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
 (figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

	<h1 style="text-align: center;">MATERIAL SAFETY DATA SHEET</h1> <p style="text-align: center;">Conforming to Reg. (EU) 878/2020</p>					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	9 di 13

12.1. Toxicity

1-methoxypropan-2-ol
 LC50 - for Fish 4600 mg/l/96h
 EC50 - for Crustacea 2954 mg/l/48h *Acartia tonsa*
 EC50 - for Algae / Aquatic Plants > 1000 mg/l/72h *Pseudokirchneriella subcapitata*
 Chronic NOEC for Crustacea 2200 mg/l/48 h *Acartia tonsa*

ETHANOLAMINE
 LC50 - for Fish 349 mg/l/96h *Cyprinus carpio*
 EC50 - for Crustacea 32,6 mg/l/48h *Daphnia magna*
 EC50 - for Algae / Aquatic Plants 2,1 mg/l/72h *Pseudokirchneriella subcapitata*
 Chronic NOEC for Fish 1,24 mg/l
 Chronic NOEC for Crustacea 0,85 mg/l
 Chronic NOEC for Algae / Aquatic Plants 1 mg/l/72 h *Pseudokirchneriella subcapitata*

3-BUTOXY-2-PROPANOL
 LC50 - for Fish 560 mg/l/96h
 EC50 - for Crustacea > 100 mg/l/48h *Daphnia magna*
 EC50 - for Algae / Aquatic Plants 519 mg/l/72h
 Chronic NOEC for Crustacea 560 mg/l/48 h *Daphnia magna*

Hydrocarbons, C3-4
 LC50 - for Fish 24,11 mg/l/96h
 EC50 - for Crustacea 14,22 mg/l/48h
 EC50 - for Algae / Aquatic Plants 7,71 mg/l/96h vale per 96h e non 72h

12.2. Persistence and degradability

1-methoxypropan-2-ol
 Rapidly degradable

ETHANOLAMINE
 Solubility in water 1000 - 10000 mg/l
 Rapidly degradable

3-BUTOXY-2-PROPANOL
 Solubility in water 52000 mg/l
 Rapidly degradable

Hydrocarbons, C3-4
 Rapidly degradable

12.3. Bioaccumulative potential

ETHANOLAMINE
 Partition coefficient: n-octanol/water -2,3
 BCF 2,3

3-BUTOXY-2-PROPANOL
 Partition coefficient: n-octanol/water 1,2

12.4. Mobility in soil

ETHANOLAMINE
 Partition coefficient: soil/water -0,5646

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	10 di 13

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.
 CONTAMINATED PACKAGING
 Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, 1950
 IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS
 IMDG: AEROSOLS
 IATA: AEROSOLS, NON-FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.2
 IMDG: Class: 2 Label: 2.2
 IATA: Class: 2 Label: 2.2



14.4. Packing group

ADR / RID, IMDG, -
 IATA:

14.5. Environmental hazards

ADR / RID: NO
 IMDG: NO
 IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (E)
IMDG:	Special provision: - EMS: F-D, S-U	Limited Quantities: 1	

	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	11 di 13

IATA:

Cargo:

L
 Maximum quantity: 150 Kg
 Maximum quantity: 75 Kg
 A98, A145, A167, A802

Packaging instructions: 203
 Packaging instructions: 203

Pass.:

Special provision:

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 3 - 40

Contained substance Point 75

Regulation (EC) No. 2019/1148 - on the marketing and use of explosives precursors
 Not applicable

Substances in Candidate List (Art. 59 REACH)
 On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)
 None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:
 None

Substances subject to the Rotterdam Convention:
 None

Substances subject to the Stockholm Convention:
 None

Healthcare controls
 Information not available

Regulation (EC) No. 648/2004
 Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)
 WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	12 di 13

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 3	Aerosol, category 3
Flam. Liq. 3	Flammable liquid, category 3
Press. Gas	Pressurised gas
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H220	Extremely flammable gas.
H229	Pressurised container: may burst if heated.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

	<h1 style="text-align: center;">MATERIAL SAFETY DATA SHEET</h1> <p style="text-align: center;">Conforming to Reg. (EU) 878/2020</p>					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Date prepared	N° rev.	Date prepared	N° rev.
171/09	23.12.2021	3	RLAB	DG	RLAB	13 di 13

- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.