 Società italiana chimica	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	2 di 12

P310 Immediately call a POISON CENTER.

Contains: hydrogen peroxide solution 7,2%
 ALCOHOLS, C12-13- BRANCHED AND LINEAR, ETHOXYLATED
 BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS

Ingredients according to Regulation (EC) No. 648/2004

Less than 5% phosphonates, anionic surfactants, non-ionic surfactants
 5% or over but less than 15% oxygen-based bleaching agents

perfumes

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
HYDROGEN PEROXIDE SOLUTION 7,2% CAS 7722-84-1 EC 231-765-0 INDEX 008-003-00-9 REACH Reg. 01-2119485845-22	$7 \leq x < 8$	Ox. Liq. 1 H271, Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1A H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: B Ox. Liq. 1 H271: \geq 70%, Ox. Liq. 2 H272: \geq 50%, Skin Corr. 1A H314: \geq 70%, Skin Corr. 1B H314: \geq 50%, Skin Irrit. 2 H315: \geq 35%, Eye Dam. 1 H318: \geq 8%, Eye Irrit. 2 H319: \geq 5% LD50 Oral: 1193 mg/kg, STA Inhalation vapours: 11 mg/l
ALCOHOLS, C12-13- BRANCHED AND LINEAR, ETHOXYLATED CAS 160901-19-9 EC 931-954-4 INDEX -	$1,5 \leq x < 2$	Acute Tox. 4 H302, Eye Dam. 1 H318, Aquatic Chronic 3 H412 Eye Dam. 1 H318: \geq 10%, Eye Irrit. 2 H319: \geq 1% STA Oral: 500 mg/kg
BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS CAS 68411-30-3 EC 270-115-0 INDEX - REACH Reg. 01-2119489428-22	$1 \leq x < 1,5$	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412 LD50 Oral: 1080 mg/kg


The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

 Società italiana chimica	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	3 di 12

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.


Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

 Società italiana chimica	<h1 style="margin: 0;">MATERIAL SAFETY DATA SHEET</h1> <p style="margin: 0;">Conforming to Reg. (EU) 878/2020</p>					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	4 di 12

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters


Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemičalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom TLV-ACGIH	EH40/2005 Workplace exposure limits (Fourth Edition 2020) ACGIH 2021

HYDROGEN PEROXIDE SOLUTION 7,2%

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV	BGR	1,5				
TLV	CZE	1	0,707	2	1,414	
MAK	DEU	0,71	0,5	0,71	0,5	
TLV	DNK	1,4	1			
VLA	ESP	1,4	1			
VLEP	FRA	1,5	1			
TLV	GRC	1,4	1	3		
GVI/KGVI	HRV	1,4	1	2,8	2	
TGG	NLD		1			
NDS/NDSch	POL	0,4		0,8		
NPFL	SVK	1,4	1	2,8	2	
MV	SVN	1,4	1	1,4	1	
WEL	GBR	1,4	1	2,8	2	
TLV-ACGIH		1,4	1			

 Società italiana chimica	<h1>MATERIAL SAFETY DATA SHEET</h1> <p>Conforming to Reg. (EU) 878/2020</p>					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	5 di 12

Predicted no-effect concentration - PNEC		
Normal value in fresh water		0,013 mg/l
Normal value in marine water		0,013 mg/l
Normal value for fresh water sediment		0,047 mg/kg
Normal value for marine water sediment		0,047 mg/kg
Normal value for water, intermittent release		0,014 mg/l
Normal value of STP microorganisms		4,66 mg/l
Normal value for the terrestrial compartment		0,002 mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	1.93 mg/m ³		0.21 mg/m ³		3 mg/m ³		1.4 mg/m ³	

BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS

Predicted no-effect concentration - PNEC		
Normal value in fresh water		0,268 mg/l
Normal value in marine water		0,027 mg/l
Normal value for fresh water sediment		8,1 mg/kg
Normal value for marine water sediment		6,8 mg/kg
Normal value for water, intermittent release		0,017 mg/l
Normal value of STP microorganisms		3,43 mg/l
Normal value for the terrestrial compartment		35 mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,425 mg/kg bw/d				
Inhalation			1,5	1,5 mg/m ³			6	6 mg/m ³
Skin				42,5 mg/kg bw/d				85 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.


EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

 Società italiana chimica	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	6 di 12

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	blue	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	3,5	
Kinematic viscosity	not available	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,02	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Explosive properties	not classified as explosive, contains no explosive substances according to CLP Art. (14 (2))
Oxidising properties	the product is not an oxidizing substance

SECTION 10. Stability and reactivity

10.1. Reactivity

HYDROGEN PEROXIDE SOLUTION 7,2%


Decomposes if exposed to: light, heat. Decomposes on contact with: alkaline metals. Possibility of explosion.

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.

		<h1>MATERIAL SAFETY DATA SHEET</h1> <p>Conforming to Reg. (EU) 878/2020</p>				Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	7 di 12

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

HYDROGEN PEROXIDE SOLUTION 7,2%

Avoid exposure to: light, heat. Avoid contact with: alkaline substances.

10.5. Incompatible materials

HYDROGEN PEROXIDE SOLUTION 7,2%

Incompatible with: flammable substances, acetone, ethanol, glycerol, organic sulphides, hydrated bases, oxidising substances, iron, copper, bronze, chromium, zinc, lead, silver, manganese, acetic acid.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:

> 20 mg/l

ATE (Oral) of the mixture:

>2000 mg/kg

ATE (Dermal) of the mixture:

Not classified (no significant component)

HYDROGEN PEROXIDE SOLUTION 7,2%

LD50 (Dermal):

> 2000 mg/kg Rabbit
at the concentration of 35%

LD50 (Oral):

1193 mg/kg Rat
at the concentration of 35%

LC50 (Inhalation vapours):

170 mg/l/4h Rat
at the concentration of 50%

STA (Inhalation vapours):

11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

ALCOHOLS, C12-13- BRANCHED AND LINEAR, ETHOXYLATED

STA (Oral):

500 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS

LD50 (Dermal):

> 2000 mg/kg rat

LD50 (Oral):

1080 mg/kg rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION


Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

		<h1 style="margin: 0;">MATERIAL SAFETY DATA SHEET</h1> <p style="margin: 0;">Conforming to Reg. (EU) 878/2020</p>				Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	8 di 12

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS

LC50 - for Fish	1,67 mg/l/96h
EC50 - for Crustacea	2,9 mg/l/48h
EC50 - for Algae / Aquatic Plants	0,91 mg/l/72h
Chronic NOEC for Fish	0,23 mg/l 72d
Chronic NOEC for Crustacea	0,5 mg/l 7d
Chronic NOEC for Algae / Aquatic Plants	0,5 mg/l 96h

HYDROGEN PEROXIDE SOLUTION 7,2%

LC50 - for Fish	16,4 mg/l/96h
EC50 - for Crustacea	2,4 mg/l/48h
EC50 - for Algae / Aquatic Plants	1,38 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	0,63 mg/l

12.2. Persistence and degradability


BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS

Rapidly degradable

HYDROGEN PEROXIDE SOLUTION 7,2%

Solubility in water	100000 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

 Società italiana chimica	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	9 di 12

BENZENESULFONIC ACID, C10-13-ALKYL
 DERIVS., SODIUM SALTS
 BCF

159

HYDROGEN PEROXIDE SOLUTION 7,2%
 Partition coefficient: n-octanol/water

-1,57

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable


14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

 Società italiana chimica	MATERIAL SAFETY DATA SHEET					Sheet Code S-P4/2-2
	Conforming to Reg. (EU) 878/2020					Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	10 di 12

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 3

Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters


15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Ox. Liq. 1	Oxidising liquid, category 1
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Eye Dam. 1	Serious eye damage, category 1

 Società italiana chimica	<h1 style="margin: 0;">MATERIAL SAFETY DATA SHEET</h1> <p style="margin: 0;">Conforming to Reg. (EU) 878/2020</p>					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	11 di 12


STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H271	May cause fire or explosion; strong oxidiser.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website

 S.I.C. srl Società italiana chimica	MATERIAL SAFETY DATA SHEET Conforming to Reg. (EU) 878/2020					Sheet Code S-P4/2-2
						Sch. Date 05/2010
						Sheet Rev.1
Document n°	Date prepared	N° rev.	Compiled by	Approved by	Filed by	Page
4/17	2.11.2022	7	RLAB	DG	RLAB	12 di 12

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 12 / 15.