NEW FADOR	MATERI		FETY [to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Rev. N°	Edited by	Page		
01/16	10.05.2022	4	RLAB	DG	RLAB	1 di 14

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Code: Product name UFI :	F_233 MARSIGLIA Liquido AMACA XVD3-00GQ-U00P-9NYE	SA	
1.2. Relevant identified uses of the substance or m	nixture and uses advised agair	ist	
Identified Uses	Industrial	Professional	Consumer
Laundry detergent	-	~	~
Uses Advised Against			
Do not use for uses other than those indicated			
1.3. Details of the supplier of the safety data sheet Name Full address District and Country	NEW FADOR S.r.I. via Mario Calderara, 31 25018 Montichiari (BS) Italia Tel. +39 030961 243 www.newfador.it		
e-mail address of the competent person			
responsible for the Safety Data Sheet	info@newfador.it		
1.4. Emergency telephone number For urgent inquiries refer to	NEW FADOR S.r.I. +39 030961 243 (08.30 - 17.30)		

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Eye irritation, category 2	H319	Causes serious eye irritation.
Classified on the basis of the study results ICE-PH-15/0339		

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning

Hazard statements:

H319

Causes serious eye irritation.

Precautionary statements:

NEW FADOR	MATERI		FETY [to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Rev. N°	Edited by	Page		
01/16	10.05.2022	4	RLAB	DG	RLAB	2 di 14

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing.
P337+P313	If eye irritation persists: Get medical advice / attention.

Ingredients according to Regulation (EC) No. 648/2004

Less than 5% soap 5% or over but less than anionic surfactants 15%

perfumes

Preservation agents: 2-Bromo-2-Nitropropane-1,3-Diol, Glutaral, Benzisothiazolinone

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\ge 0.1\%$.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification BENZENESULFONIC ACID, C10- 13-ALKYL DERIVS., SODIUM SALTS	x = Conc. %	Classification (EC) 1272/2008 (CLP)
CAS 68411-30-3	5≤x< 6	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC 270-115-0 INDEX -		LD50 Oral: 1080 mg/kg
REACH Reg. 01-2119489428-22 ALCOHOLS, C12-14, ETHOXYLATED, SULFATES,		
SODIUM SALTS CAS 68891-38-3	3≤x< 3,5	Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC 500-234-8 INDEX -		Eye Dam. 1 H318: ≥ 10%, Eye Irrit. 2 H319: ≥ 5%
REACH Reg. 01-2119488639-16 Fatty acids, coco, potassium salts		
CAS 61789-30-8	1 ≤ x < 1,5	Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC 263-049-9 INDEX -		
2-BROMO-2-NITROPROPAN-1,3- DIOL		
CAS 52-51-7	0 ≤ x < 0,05	Acute Tox. 4 H302, Acute Tox. 4 H312, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Acute 1 H400 M=10,

NEW FADOR		MATERIAL SAFETY DATA SHEET Conforms to Reg. (EU) 878/2020						
Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page		
01/16	10.05.2022	4	RLAB	DG	RLAB	3 di 14		

Aquatic Chronic 2 H411 FC 200-143-0 STA Oral: 500 mg/kg, STA Dermal: 1100 mg/kg INDEX 603-085-00-8 REACH Reg. 01-2119980938-15 MORPHOLINE CAS 110-91-8 $0 \le x < 0.05$ Flam. Liq. 3 H226, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1B H314 Eye Dam. 1 H318 LD50 Oral: 1050 mg/kg, STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 ma/l INDEX 613-028-00-9

EC 203-815-1

REACH Reg. 01-2119496057-30

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again. INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with selfcontained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

NEW FADOR		MATERIAL SAFETY DATA SHEET Conforms to Reg. (EU) 878/2020					
Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page	
01/16	10.05.2022	4	RLAB	DG	RLAB	4 di 14	

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well-ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ,
		СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари
		2020r.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se
		stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte.
		MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher
		Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών
0.10	2,01000	2017/2398/EE, 2019/130/EE και 2019/983/EE «για την τροποποίηση της οδηγίας 2004/37/EK ``σχετικά με
		την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή
		μεταλλαξιγόνους παράγοντες κατά την εργασία`»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők
non	Magyarorszag	hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu,
THEV	TITVAISKA	graničnim vrjednostima izloženosti i biološkim graničnim vrjednostima (NN 1/2021)
ITA	Italia	graniciant registrativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste
NLD	Nederland	lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Dortugol	
PRI	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes
		químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à
501	5	exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie
		w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w

NEW FADOR	MATERI	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1				
Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page
01/16	10.05.2022	4	RLAB	DG	5 di 14	

SVK	Slovensko	środowisku pracy NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s
GBR EU	United Kingdom OEL EU	expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov EH40/2005 Workplace exposure limits (Fourth Edition 2020) Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983;
	TLV-ACGIH	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. ACGIH 2021

BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS

Predicted no-effect concentrat	ion - PNEC							
Normal value in fresh water				0,268	mg	/I		
Normal value in marine water				0,027	mg	/I		
Normal value for fresh water s	ediment			8,1	mg	mg/kg		
Normal value for marine water	sediment			6,8	mg	mg/kg		
Normal value for water, intermittent release				0,017	mg	mg/l		
Normal value of STP microorganisms				3,43	mg	mg/l		
Normal value for the terrestrial compartment				35	mg/kg			
Health - Derived no-effect	t level - DNEL / D	MEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,425 mg/kg bw/d				
Inhalation			1,5	1,5 mg/m3			6	6 mg/m3
Skin				42,5 mg/kg bw/d				85 mg/kg bw/d

Predicted no-effect concern	tration - PNEC							
Normal value in fresh wate	r			0,24	mç	g/l		
Normal value in marine wa	ter			0,024	mç	g/l		
Normal value for fresh wate	er sediment			0,917	mç	g/kg		
Normal value for marine wa	ater sediment			0,092	mg	g/kg		
Normal value for water, inter	ermittent release			0,071	mg/l			
Normal value of STP micro	oorganisms			10	g/l			
Normal value for the terres	trial compartment			7,5	mg/kg			
Health - Derived no-ef	fect level - DNEL / I Effects on consumers	DMEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				15 mg/kg bw/d				
Inhalation				52 mg/m3				175 mg/m3
Skin				1650 mg/kg bw/d				2750 mg/kg bw/d

2-BROMO-2-NITROPR	ROPAN-1,3-DIOL							
Predicted no-effect concen	tration - PNEC							
Normal value in fresh wate	r			0,01	mg	g/I		
Normal value in marine wa	ter			0,001	mg	g/I		
Normal value for fresh wate	er sediment			0,041	mg	g/kg		
Normal value for marine wa	ater sediment			0,003	mg/kg			
Normal value for water, inte	ermittent release			0,003	mg/l			
Normal value of STP micro	oorganisms			0,43	mg/l			
Normal value for the terres	trial compartment			0,5	mg	g/kg		
Health - Derived no-ef	fect level - DNEL / Effects on consumers	DMEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		1,1 mg/kg bw/d		0,35 mg/kg bw/d				
Inhalation	1,3 mg/m3	3,7 mg/m3	1,3 mg/m3	1,2 mg/m3	4,2 mg/m3	12,3 mg/m3	4,2 mg/m3	4,1 mg/m3

NEW FADOR	MATERI		FETY [to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page
01/16	10.05.2022	4	RLAB	DG	RLAB	6 di 14

Skin	0,008 mg/cm2	4,2 mg/kg bw/d	0,008 mg/cm2	1,4 mg/kg bw/d	0,013 mg/cm2	7 mg/kg bw/d	0,013 mg/cm2	2,3 mg/kg bw/d
MORPHOLINE								
Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15min		Remarks / Observatio	ins	
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	20				SKIN		
TLV	CZE	35		70		SKIN		
AGW	DEU	36	10	72	20	SKIN		
MAK	DEU	36	10	72	20			
TLV	DNK	36	10			SKIN		
VLA	ESP	36	10	72	20			
VLEP	FRA	36	10	72	20			
TLV	GRC	36	10	72	20			
AK	HUN	70		70		SKIN		
GVI/KGVI	HRV	36	10	72	20	SKIN		
VLEP	ITA	36	10	72	20	SKIN		
TGG	NLD	36	10	72	20	SKIN		
VLE	PRT	36	10	72	20			
NDS/NDSCh	POL	36		72				
NPEL	SVK	36	10	72				
WEL	GBR	36	10	72	20	SKIN		
OEL	EU	36	10	72	20			
TLV-ACGIH		71	20			SKIN		
Predicted no-effect concentration	on - PNEC							
Normal value in fresh water				0,1	m	g/l		
Normal value in marine water				0,01	mg	g/l		
Normal value for fresh water se	diment			0,01	m	g/kg		
Normal value for marine water s	sediment			1,49	mg	g/kg		
Normal value for water, intermit	tent release			0,28	mg	g/l		
Normal value of STP microorga	nisms			10	mg	g/l		
Normal value for the terrestrial	compartment			0,239	mg	g/kg		
Health - Derived no-effect	level - DNEL / DI Effects on consumers	MEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
Oral		38 mg/kg bw/d		systemic 6,3 mg/kg bw/d		systemic		systemic
Inhalation	18 mg/m3		3,2 mg/m3	45 mg/m3			36 mg/m3	91 mg/m3
Skin				0,52 mg/kg bw/d			-	1,04 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards. Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

NEW FADOR	MATERI		FETY [to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page
01/16	10.05.2022	4	RLAB	DG	RLAB	7 di 14

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	white	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
рН	8.0 ± 0.5	
Kinematic viscosity	not available	
Dynamic viscosity	250 ± 50 mPa*s (25 °C; rotore 2; velocità 30)	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,012	
Relative vapour density	not available	
Particle characteristics	not applicable	
9.2. Other information		
9.2.1. Information with regard to physical ha	zard classes	
Information not available		
9.2.2. Other safety characteristics		
VOC (Directive 2010/75/EU)	0,07 % - 0,74 g/litre	
Explosive properties	not classified as explosive, contains no explosive substances according to CLP	

Oxidising properties

Art. (14 (2)) the product is not an oxidizing substance



SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BROMO-2-NITROPROPAN-1,3-DIOL Decomposes on contact with: water, metals, strong bases.

MORPHOLINE

On contact with: strong oxidising agents, reducing agents, strong acids, strong bases. May develop: heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-BROMO-2-NITROPROPAN-1,3-DIOL Avoid exposure to: light, UV rays, moisture.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

2-BROMO-2-NITROPROPAN-1,3-DIOL May develop: nitric oxide, carbon oxides, hydrobromic acid.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other info Information not available Information on likely routes of exposure Information not available Delayed and immediate effects as well as chronic effects from s Information not available Interactive effects Information not available	
ACUTE TOXICITY ATE (Inhalation) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture:	Not classified (no significant component) >2000 mg/kg Not classified (no significant component)
BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIU LD50 (Dermal): LD50 (Oral):	M SALTS > 2000 mg/kg rat 1080 mg/kg rat
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM LD50 (Dermal): LD50 (Oral):	SALTS > 2000 mg/kg rat > 2000 mg/kg rat
2-BROMO-2-NITROPROPAN-1,3-DIOL LD50 (Dermal): STA (Dermal):	64 mg/kg rat 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP

NEW FADOR	MATERI		FETY [to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page
01/16	10.05.2022	4	RLAB	DG	RLAB	9 di 14

LD50 (Oral): LC50 (Inhalation mists/powders):

MORPHOLINE

LD50 (Dermal): STA (Dermal):

LD50 (Oral): LC50 (Inhalation vapours):

SKIN CORROSION / IRRITATION Does not meet the classification criteria for this hazard class SERIOUS EYE DAMAGE / IRRITATION Causes serious eye irritation **RESPIRATORY OR SKIN SENSITISATION** Does not meet the classification criteria for this hazard class Respiratory sensitization Information not available Skin sensitization Information not available GERM CELL MUTAGENICITY Does not meet the classification criteria for this hazard class CARCINOGENICITY Does not meet the classification criteria for this hazard class REPRODUCTIVE TOXICITY Does not meet the classification criteria for this hazard class Adverse effects on sexual function and fertility Information not available Adverse effects on development of the offspring Information not available Effects on or via lactation Information not available **STOT - SINGLE EXPOSURE** Does not meet the classification criteria for this hazard class Target organs Information not available Route of exposure Information not available STOT - REPEATED EXPOSURE Does not meet the classification criteria for this hazard class Target organs Information not available Route of exposure Information not available **ASPIRATION HAZARD** Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

MORPHOLINE	
LC50 - for Fish	179 mg/l/96h
EC50 - for Crustacea	45 mg/l/48h
EC50 - for Algae / Aquatic Plants	51 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	31 mg/l 72h

2-BROMO-2-NITROPROPAN-1,3-DIOL

(figure used for calculation of the acute toxicity estimate of the mixture) 254 mg/kg rat 0,588 mg/l/4h rat

500 mg/kg Rabbit 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) 1050 mg/kg Rat 35,1 mg/l/1h Rat

NEW FADOR	
Document n°	
01/16	

MATERIAL SAFETY DATA SHEET

Conforms to Reg. (EU) 878/2020

NEW FADOR	(Board Rev. 1				
Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page
01/16	10.05.2022	4	RLAB	DG	RLAB	10 di 14

Board Code S-P4/2-2

Board Date 05/2010

LC50 - for Fish	20 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	1,6 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,25 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	0,08 mg/l
BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS	4.07.00///00/
LC50 - for Fish	1,67 mg/l/96h
EC50 - for Crustacea	2,9 mg/l/48h
EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish	0,91 mg/l/72h 0,23 mg/l 72d
Chronic NOEC for Crustacea	0,5 mg/l 7d
Chronic NOEC for Algae / Aquatic Plants	0,5 mg/l 96h
Chronic NOLO for Algae / Aqualle Frants	0,5 mg/ 30n
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS LC50 - for Fish	> 1 mg/l/96h Danio rerio
EC50 - for Crustacea	7,2 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	27 mg/l/72h Desmodesmus subspicatus
Chronic NOEC for Fish	0,14 mg/l 28d Oncorhynchus mykiss
Chronic NOEC for Crustacea	0,18 mg/l 21d Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	0.93 mg/l Desmodesmus subspicatus
12.2. Persistence and degradability	
MORPHOLINE	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
2-BROMO-2-NITROPROPAN-1,3-DIOL	
Solubility in water	286000 mg/l
Rapidly degradable	
BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable	
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable	
12.3. Bioaccumulative potential	
MORPHOLINE	
Partition coefficient: n-octanol/water	-2,55
BCF	< 2,8
2-BROMO-2-NITROPROPAN-1,3-DIOL	
Partition coefficient: n-octanol/water	0,22
BCF	3,16
BENZENESULFONIC ACID, C10-13-ALKYL	
DERIVS., SODIUM SALTS BCF	159
	139
12.4. Mobility in soil	
MORPHOLINE	
Partition coefficient: soil/water	-0,6196
ALCOHOLS, C12-14, ETHOXYLATED,	
SULFATES, SODIUM SALTS	
Partition coefficient: soil/water	0,34

NEW FADOR	MATERIAL SAFETY DATA SHEET Conforms to Reg. (EU) 878/2020					Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Page				
01/16	10.05.2022	4	RLAB	DG	RLAB	11 di 14

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

NEW FADOR	MATERIAL SAFETY DATA SHEET Conforms to Reg. (EU) 878/2020					Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Page				
01/16	10.05.2022	4	RLAB	DG	RLAB	12 di 14

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product	
Point	3 - 40

Contained substancePoint75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

<u>Substances in Candidate List (Art. 59 REACH)</u> On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH) None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None

Substances subject to the Rotterdam Convention: None

Substances subject to the Stockholm Convention: None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004 Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017) WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

NEW FADOR	MATERI	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1				
Document n°	Revision date	Page				
01/16	10.05.2022	4	RLAB	DG	RLAB	13 di 14

H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP) 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- FCHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property.

NEW FADOR	MATERI	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1				
Document n°	Revision date	Page				
01/16	10.05.2022	4	RLAB	DG	RLAB	14 di 14

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11. Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 01 / 02 / 03 / 08 / 09 / 11 / 12 / 15 / 16.