NEW FADOR	MATERI		<b>FETY [</b> to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Page				
32/16	11.09.2018	1	RLAB	DG	RLAB	1 di 12

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

<b>1.1. Product identifier</b> Code: Product name	F_239 - 036_077 MARSIGLIA Mano Lavatrice	PRIM	
1.2. Relevant identified uses of the substance or r	mixture and uses advised aga	inst	
Identified Uses	Industrial	Professional	Consumer
laundry detergent	-	<b>v</b>	<b>v</b>
Uses Advised Against			
Do not use for uses other than those indicated			
1.3. Details of the supplier of the safety data shee	t		
Name	NEW FADOR S.r.I.		
Full address	Via M. Calderara 31		
District and Country	25018 Montichiari (BS)		
	Tel. +39 030 961243		
	Fax +39 030 962500		
e-mail address of the competent person			
responsible for the Safety Data Sheet	info@newfador.it		
1.4. Emergency telephone number			
For urgent inquiries refer to	tel. +39 030 961243 (office h	nours)	
SECTION 2. Hazards identification			
2.1. Classification of the substance or mixture			

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Eye irritation, category 2	H319	Causes serious eye irritation.
Classified on the basis of the study results ICE-PH-15/0339		

# 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Warning

Hazard statements:

Signal words:

H319

Causes serious eye irritation.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing.
P337+P313	If eye irritation persists: Get medical advice / attention.

NEW FADOR		MATERIAL SAFETY DATA SHEET Conforms to Reg. (EU) 830/2015						
Document n°	Revision date	Revision date Rev. N° Edited by Approved by Filed by						
32/16	11.09.2018	1	RLAB	DG	RLAB	2 di 12		

## Ingredients according to Regulation (EC) No. 648/2004

Less than 5%	soap
5% or over but less than	anionic surfactants
15%	

#### perfumes

preservation agents : 2-Bromo-2-Nitropropane-1,3-Diol, Glutaral, Benzisothiazolinone

# 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients**

# 3.1. Substances

Information not relevant

## 3.2. Mixtures

Contains:

Identification BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS	x = Conc. %	Classification 1272/2008 (CLP)
CAS 68411-30-3	4≤x< 4,5	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315,
EC 270-115-0		Aquatic Chronic 3 H412
INDEX -		
Reg. no. 01-2119489428-22		
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS		
CAS 68891-38-3	2,5 ≤ x < 3	Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC 500-234-8		
INDEX -		
Reg. no. 01-2119488639-16		
2-BROMO-2-NITROPROPAN-1,3-DIOL		
CAS 52-51-7	0 ≤ x < 0,05	Acute Tox. 4 H302, Acute Tox. 4 H312, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Acute 1 H400 M=10, Aquatic Chronic 2 H411
EC 200-143-0		
INDEX 603-085-00-8		
Reg. no. 01-2119980938-15		
MORPHOLINE CAS 110-91-8	0 ≤ x < 0,05	Flam. Liq. 3 H226, Acute Tox. 3 H311, Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1B H314,
EC 203-815-1		Eye Dam. 1 H318

INDEX 613-028-00-9 Reg. no. 01-2119496057-30

The full wording of hazard (H) phrases is given in section 16 of the sheet.

NEW FADOR	MATERI	-	<b>FETY [</b> to Reg. (EU) 8	_	IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1		
Document n°	Revision date	Revision date Rev. N° Edited by Approved by Filed by						
32/16	11.09.2018	1	RLAB	DG	RLAB	3 di 12		

# **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again. INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

## 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters

## GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with selfcontained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6.** Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

NEW FADOR	MATERI		<b>FETY [</b> to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1		
Document n°	Revision date	Revision date Rev. N° Edited by Approved by Filed by						
32/16	11.09.2018	1	RLAB	4 di 12				

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

## 8.1. Control parameters

# Regulatory References:

DEU	Deutschland	TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2017
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos
		trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no
		trabalho - Diaro da Republica I 26; 2012-02-06
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive
		2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2018

# BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS

Predicted no-effect concentration - PNEC			
Normal value in fresh water	0,268	mg/l	
Normal value in marine water	0,027	mg/l	
Normal value for fresh water sediment	8,1	mg/kg	
Normal value for marine water sediment	6,8	mg/kg	
Normal value for water, intermittent release	0,017	mg/l	
Normal value of STP microorganisms	3,43	mg/l	
Normal value for the terrestrial compartment	35	mg/kg	

Health - Derived no-effect level - DNEL / DMEL

	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,425 mg/kg bw/d				
Inhalation			1,5	1,5 mg/m3			6	6 mg/m3
Skin				42,5 mg/kg bw/d				85 mg/kg bw/d

# ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS

Predicted no-effect concentration - PNEC			
Normal value in fresh water	0,24	mg/l	
Normal value in marine water	0,024	mg/l	
Normal value for fresh water sediment	0,917	mg/kg	
Normal value for marine water sediment	0,092	mg/kg	
Normal value for water, intermittent release	0,071	mg/l	
Normal value of STP microorganisms	10	g/l	

NEW FADOR	MATERI	_	<b>FETY [</b> to Reg. (EU) 8	_	IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page
32/16	11.09.2018	1	RLAB	DG	RLAB	5 di 12

Normal value for the terrestrial	•			7,5	mg/l	ky		
Health - Derived no-effec	t level - DNEL / DI Effects on consumers	MEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				15 mg/kg bw/d				<u> </u>
Inhalation				52 mg/m3				175 mg/m3
Skin				1650 mg/kg bw/d				2750 mg/kg bw/d
2-BROMO-2-NITROPROF								
	ION - PINEC			0.01				
Normal value in fresh water				0,01	mg/l			
Normal value in marine water				0,001	mg/l			
Normal value for fresh water so				0,041	mg/l	-		
Normal value for marine water				0,003	mg/l	-		
Normal value for water, interm				0,003	mg/l			
Normal value of STP microorg				0,43	mg/l			
Normal value for the terrestrial	•			0,5	mg/l	кд		
Health - Derived no-effec	Effects on consumers	VIEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		1,1 mg/kg bw/d		0,35 mg/kg bw/d				
Inhalation	1,3 mg/m3	3,7 mg/m3	1,3 mg/m3	1,2 mg/m3	4,2 mg/m3	12,3 mg/m3	4,2 mg/m3	4,1 mg/m3
Skin	0,008 mg/cm2	4,2 mg/kg bw/d	0,008 mg/cm2	1,4 mg/kg bw/d	0,013 mg/cm2	7 mg/kg bw/d	0,013 mg/cm2	2,3 mg/kg bw/d
MORPHOLINE								
Threshold Limit Value Type	Country	TWA/8h		STEL/15min				
1,900	oounity	mg/m3	ppm	mg/m3	ppm			
AGW	DEU	36	10	72	20	SKIN		
MAK	DEU	36	10	72	20			
VLA	ESP	36	10	72	20			
VLEP	FRA	36	10	72	20			
WEL	GBR	36	10	72	20	SKIN		
VLEP	ITA	36	10	72	20	SKIN		
OEL	NLD	36	10	72	20	SKIN		
NDS	POL	36		72				
VLE	PRT	36	10	72	20			
OEL	EU	36	10	72	20			
TLV-ACGIH		71	20			SKIN		
Predicted no-effect concentration	ion - PNEC							
Normal value in fresh water				0,1	mg/l			
Normal value in marine water				0,01	mg/l			

mg/kg Normal value for marine water sediment 1,49 mg/kg Normal value for water, intermittent release 0,28 mg/l Normal value of STP microorganisms 10 mg/l 0,239 Normal value for the terrestrial compartment mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on consumers Effects on workers Route of exposure Acute systemic Chronic local Acute local Acute local

Normal value for fresh water sediment

Chronic systemic Acute systemic Chronic systemic Chronic local Oral 38 mg/kg bw/d 6,3 mg/kg bw/d Inhalation 18 mg/m3 45 mg/m3 36 mg/m3 91 mg/m3 3,2 mg/m3

0,01

Board Code S-P4/2-2 MATERIAL SAFETY DATA SHEET Board Date 05/2010 Conforms to Reg. (EU) 830/2015 Board Rev. 1 Rev. N° Revision date Edited by Filed by Page Document n° Approved by 32/1611.09.2018 RLAB RLAB 6 di 12 1 DG

Skin

0,52 mg/kg bw/d 1,04 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must be CE marked, showing that it complies with applicable standards. Provide an emergency shower with face and eye wash station.

## HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the

duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9.** Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	white
Odour	characteristic
Odour threshold	Not available
pH	8
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	Not available
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower flammability limit	Not available
Upper flammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,01 g/ml
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	300 ± 50 mPa. Sec (rotore2; 25°C; velocità 30)
Explosive properties	not classified as explosive, contains no explosive substances according to CLP Art. (14 (2))

NEW FADOR	MATERI	-	<b>FETY [</b> to Reg. (EU) 8	_	IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1	
Document n°	Revision date	Revision date Rev. N° Edited by Approved by Filed by					
32/16	11.09.2018	1	RLAB	DG	RLAB	7 di 12	

Oxidising properties

the product is not an oxidizing substance

# 9.2. Other information

Information not available

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 2-BROMO-2-NITROPROPAN-1,3-DIOL

Decomposes on contact with: water, metals, strong bases.

# MORPHOLINE

On contact with: strong oxidising agents, reducing agents, strong acids, strong bases. May develop: heat.

# 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

# 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

# 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-BROMO-2-NITROPROPAN-1,3-DIOL

Avoid exposure to: light, UV rays, moisture.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

2-BROMO-2-NITROPROPAN-1,3-DIOL

May develop: nitric oxide, carbon oxides, hydrobromic acid.

# **SECTION 11. Toxicological information**

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information Information not available Information on likely routes of exposure Information not available Delayed and immediate effects as well as chronic effects from short and long-term exposure Information not available Interactive effects Information not available

ACUTE TOXICITY LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: >2000 mg/kg LD50 (Dermal) of the mixture:

NEW FADOR	MATERI		<b>FETY [</b> to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1	
Document n°	Revision date	Revision date Rev. N° Edited by Approved by Filed by					
32/16	11.09.2018	1	RLAB	DG	RLAB	8 di 12	

Not classified (no significant component)

MORPHOLINE LD50 (Oral) 1050 mg/kg Rat LD50 (Dermal) 500 mg/kg Rabbit LC50 (Inhalation) 35,1 mg/l/1h Rat

2-BROMO-2-NITROPROPAN-1,3-DIOL LD50 (Oral) 254 mg/kg rat LD50 (Dermal) 64 mg/kg rat LC50 (Inhalation) 0,588 mg/l/4h rat

BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS LD50 (Oral) 1080 mg/kg rat LD50 (Dermal) > 2000 mg/kg rat

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS LD50 (Oral) > 2000 mg/kg rat LD50 (Dermal) > 2000 mg/kg rat

SKIN CORROSION / IRRITATION Does not meet the classification criteria for this hazard class SERIOUS EYE DAMAGE / IRRITATION Causes serious eye irritation RESPIRATORY OR SKIN SENSITISATION Does not meet the classification criteria for this hazard class GERM CELL MUTAGENICITY Does not meet the classification criteria for this hazard class CARCINOGENICITY Does not meet the classification criteria for this hazard class REPRODUCTIVE TOXICITY Does not meet the classification criteria for this hazard class STOT - SINGLE EXPOSURE Does not meet the classification criteria for this hazard class STOT - REPEATED EXPOSURE Does not meet the classification criteria for this hazard class **ASPIRATION HAZARD** Does not meet the classification criteria for this hazard class

# **SECTION 12. Ecological information**

## 12.1. Toxicity

MORPHOLINE LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Algae / Aquatic Plants

2-BROMO-2-NITROPROPAN-1,3-DIOL LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Algae / Aquatic Plants

BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish Chronic NOEC for Crustacea Chronic NOEC for Algae / Aquatic Plants 179 mg/l/96h 45 mg/l/48h 51 mg/l/72h 31 mg/l 72h

20 mg/l/96h Oncorhynchus mykiss 1,6 mg/l/48h Daphnia magna 0,25 mg/l/72h 0,08 mg/l

1,67 mg/l/96h 2,9 mg/l/48h 0,91 mg/l/72h 0,23 mg/l 72d 0,5 mg/l 7d 0,5 mg/l 96h

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS

							Board Code S-P4/2-2	
		MATERI	AL SA	AFETY [	DATA SH	IEET	Board Date 05/2010	
	NEW FADOR		Conforms	to Reg. (EU) 8	330/2015		Board Rev. 1	
	Document n°	Revision date	Rev. N°	Edited by	Approved by	Filed by	Page	
	32/16	11.09.2018	1	RLAB	DG	RLAB	9 di 12	
EC50 - EC50 - Chronic Chronic Chronic	for Fish for Crustacea for Algae / Aquat c NOEC for Fish c NOEC for Crust c NOEC for Algae <b>rsistence and de</b> HOLINE	acea e / Aquatic Plants	<ul> <li>&gt; 1 mg/l/96h Danio rerio</li> <li>7,2 mg/l/48h Daphnia magna</li> <li>27 mg/l/72h Desmodesmus subspicatus</li> <li>0,14 mg/l 28d Oncorhynchus mykiss</li> <li>0,18 mg/l 21d Daphnia magna</li> <li>0,93 mg/l Desmodesmus subspicatus</li> </ul>					
Solubil	ity in water y degradable				1000 - 10000 mg	g/I		
Solubil	2-BROMO-2-NITROPROPAN-1,3-DIOL Solubility in water 286000 mg/l Rapidly degradable							
	BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable							
	ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable							
12.3. Bio	paccumulative p	otential						

-2,55

< 2,8

0,22

3,16

159

20.	
BENZENESULFONIC ACID, C10-13-ALKYL DERIVS. BCF	, SODIUM SALTS
12.4. Mobility in soil	
MORPHOLINE	
Partition coefficient: soil/water	

# Partition coefficient: soil/water -0,6196 ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS -0,34

## 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## 12.6. Other adverse effects

Information not available

MORPHOLINE

BCF

BCF

Partition coefficient: n-octanol/water

2-BROMO-2-NITROPROPAN-1,3-DIOL Partition coefficient: n-octanol/water

# **SECTION 13. Disposal considerations**

## 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

NEW FADOR	MATERI		<b>AFETY [</b> to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Revision date Rev. N° Edited by Approved by Filed by				
32/16	11.09.2018	1	RLAB	DG	RLAB	10 di 12

# **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

## 14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

## 14.4. Packing group

Not applicable

# 14.5. Environmental hazards

Not applicable

## 14.6. Special precautions for user

Not applicable

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

# **SECTION 15. Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point

3

Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH) None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None

Substances subject to the Rotterdam Convention: None

Substances subject to the Stockholm Convention: None

#### Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

NEW FADOR	MATERI	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1					
Document n°	Revision date	Revision date Rev. N° Edited by Approved by Filed by					
32/16	11.09.2018	1	RLAB	DG	RLAB	11 di 12	

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Lig. 3	Flammable liquid, category 3
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H226	Flammable liquid and vapour.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labelling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value

	MATERI	Board Code S-P4/2-2 Board Date 05/2010				
<b>NEW FADOR</b>	(	Board Rev. 1				
Document n°	Revision date	Page				
32/16	11.09.2018	1	RLAB	DG	RLAB	12 di 12

- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.

- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 7
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP) 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.