NEW FADOR	MATERIAL SAFETY DATA SHEET					Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1	
Document n°	Revision date	Page					
31/19	19.11.2019	1	RLAB	DG	RLAB	1 di 12	

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Code: Product name	F_191 - 036_062 LAVATRICE Marsig	lia PRIM	
1.2. Relevant identified uses of the substar	nce or mixture and uses advi	ised against	
Identified Uses	Industrial	Professional	Consumer
laundry detergent	-	×	v
Uses Advised Against			
Do not use for uses other than those indicated	t de la constante de		
1.3. Details of the supplier of the safety dat Name Full address District and Country	NEW FADOR S.r.I. Via M. Calderara 31 25018 Montichiari (Tel. +39 030 961243 Fax +39 030 962500	BS)	
e-mail address of the competent person			
responsible for the Safety Data Sheet	info@newfador.it		
1.4. Emergency telephone number For urgent inquiries refer to	tel. +39 030 961243	(office hours)	
SECTION 2. Hazards identificat	ion		

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Eye irritation, category 2	H319	Causes serious eye irritation.
Classified on the basis of the results of the ICE-PH-15/03	39	
study		

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Warning

Hazard statements:


Signal words:

H319

Causes serious eye irritation.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice / attention.



Ingredients according to Regulation (EC) No. 648/2004

Less than 5% non-ionic surfactants, soap 5% or over but less than anionic surfactants 15%

perfumes

preservation agents : OCTYLISOTHIAZOLINONE, BENZISOTHIAZOLINONE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS	x = Conc. %	Classification 1272/2008 (CLP)
CAS 68411-30-3	4≤x< 4,5	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC 270-115-0 INDEX -		
Reg. no. 01-2119489428-22		
ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED		
CAS 160901-19-9	1,5≤x< 2	Acute Tox. 4 H302, Eye Dam. 1 H318, Aquatic Chronic 3 H412
EC 931-954-4		· · · · · · · · · · · · · · · · · · ·
INDEX -		
Reg. no. 01-2119490233-42		
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS		
CAS 68891-38-3	1 ≤ x < 1,5	Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC 500-234-8		
INDEX -		
Reg. no. 01-2119488639-16		
MORPHOLINE		
CAS 110-91-8	0 ≤ x < 0,05	Flam. Liq. 3 H226, Acute Tox. 3 H311, Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318
EC 203-815-1		-
INDEX 613-028-00-9		

INDEX 613-028-00-9

Reg. no. 01-2119496057-30

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

NEW FADOR	MATERI		FETY [to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1	
Document n°	Revision date	Revision date Rev. n° Edited by Approved by Filed by					
31/19	19.11.2019	1	RLAB	DG	RLAB	3 di 12	

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again. INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with selfcontained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

NEW FADOR	MATERI	_	FETY [to Reg. (EU) 8	_	IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1	
Document n°	Revision date	Revision date Rev. n° Edited by Approved by Filed by					
31/19	19.11.2019	1	RLAB	DG	RLAB	4 di 12	

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU ESP	Deutschland España	TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte INSHT - Límites de exposición profesional para agentes guímicos en España 2017
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2017

BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS

Predicted no-effect concent	ration - PNEC							
Normal value in fresh water				0,268	mg	g/l		
Normal value in marine water			0,027	mç	g/l			
Normal value for fresh water sediment			8,1	mg	g/kg			
Normal value for marine water sediment			6,8	mg	g/kg			
Normal value for water, intermittent release			0,017	mg/l				
Normal value of STP microorganisms			3,43	mg/l				
Normal value for the terrestrial compartment			35	mg	g/kg			
Health - Derived no-eff	fect level - DNEL / I	DMEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,425 mg/kg bw/d				
Inhalation			1,5	1,5 mg/m3			6	6 mg/m3
Skin				42,5 mg/kg bw/d				85 mg/kg bw/d

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS

Predicted no-effect concentration - PNEC			
Normal value in fresh water	0,24	mg/l	
Normal value in marine water	0,024	mg/l	
Normal value for fresh water sediment	0,917	mg/kg	
Normal value for marine water sediment	0,092	mg/kg	
Normal value for water, intermittent release	0,071	mg/l	
Normal value of STP microorganisms	10	g/l	
Normal value for the terrestrial compartment	7,5	mg/kg	

NEW FADOR	MATERI		FETY [to Reg. (EU) 8		IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1	
Document n°	Revision date	Page					
31/19	19.11.2019	1	RLAB	DG	RLAB	5 di 12	

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				15 mg/kg bw/d				
Inhalation				52 mg/m3				175 mg/m3
Skin				1650 mg/kg bw/d				2750 mg/kg bw/d
MORPHOLINE Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	36	10	72	20	SKIN		
MAK	DEU	36	10	72	20			
VLA	ESP	36	10	72	20			
VLEP	FRA	36	10	72	20			
WEL	GBR	36	10	72	20	SKIN		
VLEP	ITA	36	10	72	20	SKIN		
OEL	NLD	36	10	72	20	SKIN		
NDS	POL	36		72				
VLE	PRT	36	10	72	20			
OEL	EU	36	10	72	20			
TLV-ACGIH		71	20			SKIN		
Predicted no-effect concentra	ation - PNEC							
Normal value in fresh water				0,1	m	g/I		
Normal value in marine wate	r			0,01	m	g/I		
Normal value for fresh water	sediment			0,01	m	g/kg		
Normal value for marine wate	er sediment			1,49	m	g/kg		
Normal value for water, interr	mittent release			0,28	m	g/l		
Normal value of STP microor	ganisms			10	m	g/l		
Normal value for the terrestria	al compartment			0,239	m	g/kg		
Health - Derived no-effe	ect level - DNEL / I Effects on consumers	DMEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		38 mg/kg bw/d		6,3 mg/kg bw/d				
Inhalation	18 mg/m3		3,2 mg/m3	45 mg/m3			36 mg/m3	91 mg/m3

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must be CE marked, showing that it complies with applicable standards. Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

NEW FADOR	MATERI	_	FETY [to Reg. (EU) 8	_	IEET	Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Page				
31/19	19.11.2019	1	RLAB	DG	RLAB	6 di 12

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the

threshold values considered. The protection provided by masks is nany case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colour Odour Odour threshold pH Melting point / freezing point Initial boiling point Boiling range Flash point Evaporation rate Flammability (solid, gas) Lower flammability limit Upper flammability limit Lower explosive limit Upper explosive limit Upper explosive limit Vapour pressure Vapour density Belative density	liquid opalescent white characteristic Not available 8,5 Not available Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,007 g/ml
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	150 ± 50 mPa. Sec (rotor2; 25 ° C; speed 30)
Explosive properties	not classified as explosive, contains no explosive substances according to CLP Art. (14 (2))
Oxidising properties	the product is not an oxidizing substance

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

MORPHOLINE

On contact with: strong oxidising agents, reducing agents, strong acids, strong bases. May develop: heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

NEW FADOR	MATERIAL SAFETY DATA SHEET Conforms to Reg. (EU) 830/2015					Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Page				
31/19	19.11.2019	1	RLAB	DG	RLAB	7 di 12

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information Information not available Information on likely routes of exposure Information not available Delayed and immediate effects as well as chronic effects from short and long-term exposure Information not available Interactive effects Information not available

ACUTE TOXICITY LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: >2000 mg/kg LD50 (Dermal) of the mixture: Not classified (no significant component)

MORPHOLINE LD50 (Oral) 1050 mg/kg Rat LD50 (Dermal) 500 mg/kg Rabbit LC50 (Inhalation) 35,1 mg/l/1h Rat

ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED LD50 (Oral) > 300 mg/kg rat LD50 (Dermal) > 2000 mg/kg rabbit

BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS LD50 (Oral) 1080 mg/kg rat LD50 (Dermal) > 2000 mg/kg rat

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS LD50 (Oral) > 2000 mg/kg rat LD50 (Dermal) > 2000 mg/kg rat

 SKIN CORROSION / IRRITATION

 Does not meet the classification criteria for this hazard class

 SERIOUS EYE DAMAGE / IRRITATION

 Causes serious eye irritation

 RESPIRATORY OR SKIN SENSITISATION

 Does not meet the classification criteria for this hazard class

 GERM CELL MUTAGENICITY

 Does not meet the classification criteria for this hazard class

 CARCINOGENICITY

 Does not meet the classification criteria for this hazard class

 CARCINOGENICITY

 Does not meet the classification criteria for this hazard class

 REPRODUCTIVE TOXICITY

 Does not meet the classification criteria for this hazard class

 STOT - SINGLE EXPOSURE

NEW FADOR	Conforms to Reg. (EU) 830/2015					Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Page				
31/19	19.11.2019	1	RLAB	DG	RLAB	8 di 12

Does not meet the classification criteria for this hazard class <u>STOT - REPEATED EXPOSURE</u> Does not meet the classification criteria for this hazard class <u>ASPIRATION HAZARD</u> Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

12.1. Toxicity

MORPHOLINE	
LC50 - for Fish	179 mg/l/96h
EC50 - for Crustacea	45 mg/l/48h
EC50 - for Algae / Aquatic Plants	51 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	31 mg/l 72h
ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED	
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h Desmodesmus subspicatus
EC10 for Crustacea	> 0,1 mg/l Daphnia magna
BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS	
LC50 - for Fish	1,67 mg/l/96h
EC50 - for Crustacea	2,9 mg/l/48h
EC50 - for Algae / Aquatic Plants	0,91 mg/l/72h
Chronic NOEC for Fish	0,23 mg/l 72d
Chronic NOEC for Crustacea	0,5 mg/l 7d
Chronic NOEC for Algae / Aquatic Plants	0,5 mg/l 96h
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS	
LC50 - for Fish	> 1 mg/l/96h Danio rerio
EC50 - for Crustacea	7,2 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	27 mg/l/72h Desmodesmus subspicatus
Chronic NOEC for Fish	0,14 mg/l 28d Oncorhynchus mykiss
Chronic NOEC for Crustacea	0,18 mg/l 21d Daphnia magna
	0,93 mg/l Desmodesmus subspicatus
Chronic NOEC for Algae / Aquatic Plants	
Chronic NOEC for Algae / Aquatic Plants	0,95 mg/i Desmodesmus subspicatus
	0,95 mg/ Desmodesmus subspicatus
12.2. Persistence and degradability	0,95 mgr Desmodesmus subspicatus
	0,35 mgr Desmodesmus subspicatus
12.2. Persistence and degradability	1000 - 10000 mg/l
12.2. Persistence and degradability MORPHOLINE	
12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable	
12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED	
12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable	
12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable	
12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS	
12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable	
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable 	
12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS	
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable 	
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS 	
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable 12.3. Bioaccumulative potential 	
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable 12.3. Bioaccumulative potential MORPHOLINE 	1000 - 10000 mg/l
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable 12.3. Bioaccumulative potential MORPHOLINE Partition coefficient: n-octanol/water 	1000 - 10000 mg/l
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable 12.3. Bioaccumulative potential MORPHOLINE 	1000 - 10000 mg/l
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable 12.3. Bioaccumulative potential MORPHOLINE Partition coefficient: n-octanol/water BCF 	1000 - 10000 mg/l
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable 12.3. Bioaccumulative potential MORPHOLINE Partition coefficient: n-octanol/water BCF BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS 	-2,55 < 2,8
 12.2. Persistence and degradability MORPHOLINE Solubility in water Rapidly degradable ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Rapidly degradable BENZENESULFONIC ACID, C10-13-ALKYL DERIVS., SODIUM SALTS Rapidly degradable ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Rapidly degradable 12.3. Bioaccumulative potential MORPHOLINE Partition coefficient: n-octanol/water BCF 	1000 - 10000 mg/l

NEW FADOR	MATERIAL SAFETY DATA SHEET					Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Page				
31/19	19.11.2019	9 di 12				

12.4. Mobility in soil

MORPHOLINE Partition coefficient: soil/water	-0,6196
ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED Partition coefficient: soil/water	3,69
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS Partition coefficient: soil/water	0,34

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable


14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code



SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point

3

<u>Substances in Candidate List (Art. 59 REACH)</u> On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH) None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None

Substances subject to the Rotterdam Convention: None

Substances subject to the Stockholm Convention: None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

German regulation on the classification of substances hazardous to water (VwVwS 2005) WGK 2: Hazard to waters

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H226	Flammable liquid and vapour.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.

NEW FADOR	MATERIAL SAFETY DATA SHEET					Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Filed by	Page			
31/19	19.11.2019	1	RLAB	DG	RLAB	11 di 12

- H314 Causes severe skin burns and eye damage. H318
- Causes serious eye damage.
- H319 Causes serious eye irritation.
- H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labelling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

NEW FADOR	MATERIAL SAFETY DATA SHEET					Board Code S-P4/2-2 Board Date 05/2010 Board Rev. 1
Document n°	Revision date	Page				
31/19	19.11.2019	1	RLAB	DG	RLAB	12 di 12

Section modified to previous edition: 02 / 03 / 08 / 10 / 12 / 16.